

CMU SCS

Carnegie Mellon Univ. Dept. of Computer Science 15-415 - Database Applications

Schema Refinement & Normalization -
Normal Forms
(R&G, ch. 19)

CMU SCS

Overview - detailed

- DB design and normalization
 - pitfalls of bad design
 - decomposition
 - normal forms

Faloutsos CMU SCS 15-415 2

CMU SCS

Goal

- Design ‘good’ tables
 - sub-goal#1: define what ‘good’ means
 - sub-goal#2: fix ‘bad’ tables
- in short: “*we want tables where the attributes depend on the primary key, on the whole key, and nothing but the key*”
- Let’s see why, and how:

Faloutsos CMU SCS 15-415 3

CMU SCS

Pitfalls

takes1 (ssn, c-id, grade, name, address)

| Ssn | c-id | Grade | Name | Address |
|-----|------|-------|-------|---------|
| 123 | 413 | A | smith | Main |

Faloutsos CMU SCS 15-415 4

CMU SCS

Pitfalls

‘Bad’ - why? because: ssn->address, name

| Ssn | c-id | Grade | Name | Address |
|-----|------|-------|-------|---------|
| 123 | 413 | A | smith | Main |
| 123 | 415 | B | smith | Main |
| 123 | 211 | A | smith | Main |

Faloutsos CMU SCS 15-415 5

CMU SCS

Pitfalls

- Redundancy
 - space
 - (inconsistencies)
 - insertion/deletion anomalies:

Faloutsos CMU SCS 15-415 6

Pitfalls

- insertion anomaly:
 - “jones” registers, but takes no class - no place to store his address!

| Ssn | c-id | Grade | Name | Address |
|-----|------|-------|-------|---------|
| 123 | 413 | A | smith | Main |
| ... | ... | ... | ... | ... |
| 234 | Ⓝ | null | jones | Forbes |

Faloutsos CMU SCS 15-415 7

Pitfalls

- deletion anomaly:
 - delete the last record of ‘smith’ (we lose his address!)

| Ssn | c-id | Grade | Name | Address |
|-----|------|-------|-------|---------|
| 123 | 413 | A | smith | Main |
| 123 | 415 | B | smith | Main |
| 123 | 211 | A | smith | Main |

Faloutsos CMU SCS 15-415 8

Solution: decomposition

- split offending table in two (or more), eg.:

| Ssn | c-id | Grade | Name | Address |
|-----|------|-------|-------|---------|
| 123 | 413 | A | smith | Main |
| 123 | 415 | B | smith | Main |
| 123 | 211 | A | smith | Main |

Faloutsos CMU SCS 15-415 9

Overview - detailed

- DB design and normalization
 - pitfalls of bad design
 - decomposition
 - lossless join decomp.
 - dependency preserving
 - normal forms

Faloutsos CMU SCS 15-415 10

Decompositions

There are ‘bad’ decompositions. Good ones are:

- lossless and
- dependency preserving

Faloutsos CMU SCS 15-415 11

Decompositions - lossy:

R1(ssn, grade, name, address)

| Ssn | Grade | Name | Address |
|-----|-------|-------|---------|
| 123 | A | smith | Main |
| 123 | B | smith | Main |
| 234 | A | jones | Forbes |

R2(c-id, grade)

| c-id | Grade |
|------|-------|
| 413 | A |
| 415 | B |
| 211 | A |

| Ssn | c-id | Grade | Name | Address |
|-----|------|-------|-------|---------|
| 123 | 413 | A | smith | Main |
| 123 | 415 | B | smith | Main |
| 234 | 211 | A | jones | Forbes |

ssn->name, address

ssn, c-id -> grade

Faloutsos CMU SCS 15-415 12

Decompositions - lossy:

can not recover original table with a join!

| Ssn | Grade | Name | Address |
|-----|-------|-------|---------|
| 123 | A | smith | Main |
| 123 | B | smith | Main |
| 234 | A | jones | Forbes |

| c-id | Grade |
|------|-------|
| 413 | A |
| 415 | B |
| 211 | A |

| Ssn | c-id | Grade | Name | Address |
|-----|------|-------|-------|---------|
| 123 | 413 | A | smith | Main |
| 123 | 415 | B | smith | Main |
| 234 | 211 | A | jones | Forbes |

ssn->name, address
ssn, c-id -> grade

Faloutsos CMU SCS 15-415 13

Decompositions

example of non-dependency preserving

| S# | address | status |
|-----|---------|--------|
| 123 | London | E |
| 125 | Paris | E |
| 234 | Pitts. | A |

| S# | address |
|-----|---------|
| 123 | London |
| 125 | Paris |
| 234 | Pitts. |

| S# | status |
|-----|--------|
| 123 | E |
| 125 | E |
| 234 | A |

S# -> address, status
address -> status

S# -> address **S# -> status**

Faloutsos CMU SCS 15-415 14

Decompositions

(drill: is it lossless?)

| S# | address | status |
|-----|---------|--------|
| 123 | London | E |
| 125 | Paris | E |
| 234 | Pitts. | A |

| S# | address |
|-----|---------|
| 123 | London |
| 125 | Paris |
| 234 | Pitts. |

| S# | status |
|-----|--------|
| 123 | E |
| 125 | E |
| 234 | A |

S# -> address, status
address -> status

S# -> address **S# -> status**

Faloutsos CMU SCS 15-415 15

Decompositions - lossless

Definition:
consider schema R, with FD 'F'. R1, R2 is a lossless join decomposition of R if we **always** have: $r1 \bowtie r2 = r$

An easier criterion?

Faloutsos CMU SCS 15-415 16

Decomposition - lossless

Theorem: lossless join decomposition if the joining attribute is a superkey in at least one of the new tables

Formally:

$R1 \cap R2 \rightarrow R1$ or
 $R1 \cap R2 \rightarrow R2$

Faloutsos CMU SCS 15-415 17

Decomposition - lossless

example:

| Ssn | c-id | Grade |
|-----|------|-------|
| 123 | 413 | A |
| 123 | 415 | B |
| 234 | 211 | A |

| Ssn | Name | Address |
|-----|-------|---------|
| 123 | smith | Main |
| 234 | jones | Forbes |

ssn, c-id -> grade **ssn->name, address**

| Ssn | c-id | Grade | Name | Address |
|-----|------|-------|-------|---------|
| 123 | 413 | A | smith | Main |
| 123 | 415 | B | smith | Main |
| 234 | 211 | A | jones | Forbes |

ssn->name, address
ssn, c-id -> grade

Faloutsos CMU SCS 15-415 18

CMU SCS

Overview - detailed

- DB design and normalization
 - pitfalls of bad design
 - decomposition
 - lossless join decomp.
 - **dependency preserving**
 - normal forms

Faloutsos CMU SCS 15-415 19

CMU SCS

Decomposition - depend. pres.

informally: we don't want the original FDs to span two tables - counter-example:

| S# | address | status |
|-----|---------|--------|
| 123 | London | E |
| 125 | Paris | E |
| 234 | Pitts. | A |

| S# | address |
|-----|---------|
| 123 | London |
| 125 | Paris |
| 234 | Pitts. |

| S# | status |
|-----|--------|
| 123 | E |
| 125 | E |
| 234 | A |

S# -> address, status
address -> status

S# -> address **S# -> status**

Faloutsos CMU SCS 15-415 20

CMU SCS

Decomposition - depend. pres.

dependency preserving decomposition:

| S# | address | status |
|-----|---------|--------|
| 123 | London | E |
| 125 | Paris | E |
| 234 | Pitts. | A |

| S# | address |
|-----|---------|
| 123 | London |
| 125 | Paris |
| 234 | Pitts. |

| address | status |
|---------|--------|
| London | E |
| Paris | E |
| Pitts. | A |

S# -> address, status
address -> status

S# -> address **address -> status**
(but: S#->status ?)

Faloutsos CMU SCS 15-415 21

CMU SCS

Decomposition - depend. pres.

informally: we don't want the original FDs to span two tables.

More specifically: ... the FDs of the **canonical cover**.

Faloutsos CMU SCS 15-415 22

CMU SCS

Decomposition - depend. pres.

why is dependency preservation good?

| S# | address |
|-----|---------|
| 123 | London |
| 125 | Paris |
| 234 | Pitts. |

| S# | status |
|-----|--------|
| 123 | E |
| 125 | E |
| 234 | A |

| S# | address |
|-----|---------|
| 123 | London |
| 125 | Paris |
| 234 | Pitts. |

| address | status |
|---------|--------|
| London | E |
| Paris | E |
| Pitts. | A |

S# -> address
S# -> status
(address->status: 'lost')

S# -> address **address -> status**

Faloutsos CMU SCS 15-415 23

CMU SCS

Decomposition - depend. pres.

A: eg., record that 'Philly' has status 'A'

| S# | address |
|-----|---------|
| 123 | London |
| 125 | Paris |
| 234 | Pitts. |

| S# | status |
|-----|--------|
| 123 | E |
| 125 | E |
| 234 | A |

| S# | address |
|-----|---------|
| 123 | London |
| 125 | Paris |
| 234 | Pitts. |

| address | status |
|---------|--------|
| London | E |
| Paris | E |
| Pitts. | A |

S# -> address
S# -> status
(address->status: 'lost')

S# -> address **address -> status**

Faloutsos CMU SCS 15-415 24

CMU SCS

Decomposition - conclusions

- decompositions should always be lossless
 - joining attribute -> superkey
- whenever possible, we want them to be dependency preserving (occasionally, impossible - see 'STJ' example later...)

Faloutsos CMU SCS 15-415 25

CMU SCS

Overview - detailed

- DB design and normalization
 - pitfalls of bad design
 - decomposition (-> how to fix the problem)
 - **normal forms** (-> how to detect the problem)
 - BCNF,
 - 3NF
 - (1NF, 2NF)

Faloutsos CMU SCS 15-415 26

CMU SCS

Normal forms - BCNF

We saw how to fix 'bad' schemas - but what is a 'good' schema?

Answer: 'good', if it obeys a 'normal form', ie., a set of rules.

Typically: Boyce-Codd Normal form

Faloutsos CMU SCS 15-415 27

CMU SCS

Normal forms - BCNF

Defn.: Rel. R is in BCNF wrt F, if

- informally: everything depends on the full key, and nothing but the key
- semi-formally: every determinant (of the cover) is a candidate key

Faloutsos CMU SCS 15-415 28

CMU SCS

Normal forms - BCNF

Example and counter-example:

| Ssn | Name | Address |
|-----|-------|---------|
| 123 | smith | Main |
| 999 | smith | Shady |
| 234 | jones | Forbes |

ssn->name, address

| Ssn | c-id | Grade | Name | Address |
|-----|------|-------|-------|---------|
| 123 | 413 | A | smith | Main |
| 123 | 415 | B | smith | Main |
| 234 | 211 | A | jones | Forbes |

ssn->name, address
ssn, c-id -> grade

Faloutsos CMU SCS 15-415 29

CMU SCS

Normal forms - BCNF

Formally: for every FD $a \rightarrow b$ in F

- $a \rightarrow b$ is trivial (a superset of b) or
- a is a superkey

Faloutsos CMU SCS 15-415 30

CMU SCS

Normal forms - BCNF

Theorem: given a schema R and a set of FD 'F', we can always decompose it to schemas R1, ... Rn, so that

- R1, ... Rn are in BCNF and
- the decompositions are lossless.

(but, some decomp. might lose dependencies)

Faloutsos CMU SCS 15-415 31

CMU SCS

Normal forms - BCNF

How? algorithm in book: for a relation R

- for every FD $X \rightarrow A$ that violates BCNF, decompose to tables (X,A) and (R-A)
- repeat recursively

eg. TAKES1(ssn, c-id, grade, name, address)

ssn \rightarrow name, address
 ssn, c-id \rightarrow grade

Faloutsos CMU SCS 15-415 32

CMU SCS

Normal forms - BCNF

eg. TAKES1(ssn, c-id, grade, name, address)

ssn \rightarrow name, address ssn, c-id \rightarrow grade

Faloutsos CMU SCS 15-415 33

CMU SCS

Normal forms - BCNF

| Ssn | c-id | Grade |
|-----|------|-------|
| 123 | 413 | A |
| 123 | 415 | B |
| 234 | 211 | A |

| Ssn | Name | Address |
|-----|-------|---------|
| 123 | smith | Main |
| 123 | smith | Main |
| 234 | jones | Forbes |

ssn, c-id \rightarrow grade **ssn \rightarrow name, address**

| Ssn | c-id | Grade | Name | Address |
|-----|------|-------|-------|---------|
| 123 | 413 | A | smith | Main |
| 123 | 415 | B | smith | Main |
| 234 | 211 | A | jones | Forbes |

ssn \rightarrow name, address
ssn, c-id \rightarrow grade

Faloutsos CMU SCS 15-415 34

CMU SCS

Normal forms - BCNF

pictorially: we want a 'star' shape

:not in BCNF

Faloutsos CMU SCS 15-415 35

CMU SCS

Normal forms - BCNF

pictorially: we want a 'star' shape

Faloutsos CMU SCS 15-415 36

CMU SCS

Normal forms - BCNF

or a star-like: (eg., 2 cand. keys):
 STUDENT(ssn, st#, name, address)

Faloutsos CMU SCS 15-415 37

CMU SCS

Normal forms - BCNF

but **not**:

Faloutsos CMU SCS 15-415 38

CMU SCS

Normal forms - 3NF

consider the 'classic' case:
 STJ(Student, Teacher, subJect)

$T \rightarrow J$
 $S, J \rightarrow T$

is it BCNF?

Faloutsos CMU SCS 15-415 39

CMU SCS

Normal forms - 3NF

STJ(Student, Teacher, subJect)

$T \rightarrow J$ $S, J \rightarrow T$

How to decompose it to BCNF?

Faloutsos CMU SCS 15-415 40

CMU SCS

Normal forms - 3NF

STJ(Student, Teacher, subJect)

$T \rightarrow J$ $S, J \rightarrow T$

1) $R_1(T, J)$ $R_2(S, J)$
 (BCNF? - lossless? - dep. pres.?)

2) $R_1(T, J)$ $R_2(S, T)$
 (BCNF? - lossless? - dep. pres.?)

Faloutsos CMU SCS 15-415 41

CMU SCS

Normal forms - 3NF

STJ(Student, Teacher, subJect)

$T \rightarrow J$ $S, J \rightarrow T$

1) $R_1(T, J)$ $R_2(S, J)$
 (BCNF? **Y+Y** - lossless? **N** - dep. pres.? **N**)

2) $R_1(T, J)$ $R_2(S, T)$
 (BCNF? **Y+Y** - lossless? **Y** - dep. pres.? **N**)

Faloutsos CMU SCS 15-415 42

CMU SCS

Normal forms - 3NF

STJ(Student, Teacher, subJect)
 $T \rightarrow J \quad S, J \rightarrow T$

in this case: impossible to have both

- BCNF **and**
- dependency preservation


Welcome 3NF!

Faloutsos CMU SCS 15-415 43

CMU SCS

Normal forms - 3NF

STJ(Student, Teacher, subJect)
 $T \rightarrow J \quad S, J \rightarrow T$




informally, 3NF
 'forgives' the red arrow
 in the can. cover

Faloutsos CMU SCS 15-415 44

CMU SCS

Normal forms - 3NF

STJ(Student, Teacher, subJect)
 $T \rightarrow J \quad S, J \rightarrow T$



Formally, a rel. R with FDs 'F' is in 3NF if:
 for every $a \rightarrow b$ in F:

- it is trivial or
- a is a superkey or
- b : part of a candidate key

Faloutsos CMU SCS 15-415 45

CMU SCS

Normal forms - 3NF

how to bring a schema to 3NF?
 two algo's in book: First one:

- start from ER diagram and turn to tables
- then we have a set of tables R_1, \dots, R_n which are in 3NF
- for each FD $(X \rightarrow A)$ in the cover that is not preserved, create a table (X, A)

Faloutsos CMU SCS 15-415 46

CMU SCS

Normal forms - 3NF

how to bring a schema to 3NF?
 two algo's in book: Second one ('synthesis')

- take all attributes of R
- for each FD $(X \rightarrow A)$ in the cover, add a table (X, A)
- if not lossless, add a table with appropriate key

Faloutsos CMU SCS 15-415 47

CMU SCS

Normal forms - 3NF

Example:
 R: ABC
 F: $A \rightarrow B, C \rightarrow B$

Q1: what is the cover?
 Q2: what is the decomposition to 3NF?

Faloutsos CMU SCS 15-415 48

CMU SCS

Normal forms - 3NF

Example:
 R: ABC
 F: A->B, C->B
 Q1: what is the cover?
 A1: 'F' is the cover
 Q2: what is the decomposition to 3NF?

Faloutsos CMU SCS 15-415 49

CMU SCS

Normal forms - 3NF

Example:
 R: ABC
 F: A->B, C->B
 Q1: what is the cover?
 A1: 'F' is the cover
 Q2: what is the decomposition to 3NF?
 A2: R1(A,B), R2(C,B), ... [is it lossless??]

Faloutsos CMU SCS 15-415 50

CMU SCS

Normal forms - 3NF

Example:
 R: ABC
 F: A->B, C->B
 Q1: what is the cover?
 A1: 'F' is the cover
 Q2: what is the decomposition to 3NF?
 A2: R1(A,B), R2(C,B), R3(A,C)

Faloutsos CMU SCS 15-415 51

CMU SCS

Normal forms - 3NF vs BCNF

- If 'R' is in BCNF, it is always in 3NF (but not the reverse)
- In practice, aim for
 - BCNF; lossless join; and dep. preservation
- if impossible, we accept
 - 3NF; but insist on lossless join and dep. preservation

Faloutsos CMU SCS 15-415 52

CMU SCS

Normal forms - more details

- why '3'NF? what is 2NF? 1NF?
- 1NF: attributes are atomic (ie., no set-valued attr., a.k.a. 'repeating groups')

| Ssn | Name | Dependents |
|-----|-------|-----------------------|
| 123 | Smith | Peter Mary John |
| 234 | Jones | Ann Michael |

not 1NF

Faloutsos CMU SCS 15-415 53

CMU SCS

Normal forms - more details

2NF: 1NF and non-key attr. fully depend on the key

counter-example: TAKESI(ssn, c-id, grade, name, address)
 ssn -> name, address ssn, c-id -> grade

Faloutsos CMU SCS 15-415 54

CMU SCS

Normal forms - more details

- 3NF: 2NF and no transitive dependencies
- counter-example:

```

graph LR
    A[A] --> B[B]
    A[A] --> C[C]
    B[B] --> D[D]
    D[D] --> C[C]
  
```

in 2NF, but **not** in 3NF

Faloutsos CMU SCS 15-415 55

CMU SCS

Normal forms - more details

- 4NF, multivalued dependencies etc: IGNORE
- in practice, E-R diagrams usually lead to tables in BCNF

Faloutsos CMU SCS 15-415 56

CMU SCS

Overview - conclusions

DB design and normalization

- pitfalls of bad design
- decompositions (lossless, dep. preserving)
- normal forms (BCNF or 3NF)

“everything should depend on the key, the **whole** key, and **nothing but** the key”

Faloutsos CMU SCS 15-415 57