



### VIVID 91, the most accurate VIVID yet

Introducing the latest addition to Konica Minolta's VIVID Series.

### Featuring improved accuracy and usability and flexibility. Offering unprecedented value.

It's the most advanced model for industrial applications from reverse engineering to design verification and dimensional inspection.

The essentials of imaging

vivia 9i

# **Digital Process Re-engineering**

Introducing the VIVID 9i non-contact 3D digitizer. This innovative device is ideal for reverse engineering, design verification, quality inspection, and other industrial applications.

**The VIVID 9i** non-contact 3D digitizer provides high-speed and high-accuracy 3D measurement of dies, cast and forged products, and stamped and plastic-molded products. The 9i excels at shape evaluation, tool and die qualification, and quality inspection during prototype creation and the during the production processes. The 9i is an ideal way to capture the shape and dimensional data of design models and prototypes in design drawings for reverse engineering purposes.

When used for reverse engineering or CAE, the VIVID 9i easily and accurately converts the shape of a product into 3D digital data. Using the VIVID 9i for inspection or CAT contributes to the early detection of shape problems, provides rapid feedback on design, and eliminates unnecessary work in downstream processes. As a result, it accelerates the entire manufacturing process.

Smooth input and output of 3D digital data are essential to increasing work efficiency during the design, manufacturing, and inspection processes. By introducing the VIVID 9i, Konica Minolta has accelerated the revolution in manufacturing - a sector committed to the use of digital processing tools such as CAD, CAM, and CAE, to higher-quality shape input and process output, and to reduced throughput time. That's why we're promoting "**Digital Process Re-engineering**," with the goal of improved effeiciency, and ultimately of enhanced customer satisfaction.



## VIVID 9i system

### VIVID 9i (Polygon Editing Tool Ver.2.0)

#### Measure targets of any size.

Konica Minolta employed its expertise in optical engineering to develop interchangeable highperformance, dedicated lenses. As a result, TELE, MIDDLE and WIDE lenses can be selected to accommodate the size of the measurement target.

(Input range in X, Y and Z directions: 93 x 69 x 26 mm to 1495 x 1121 x 1750 mm)

#### Point & Shoot, Leave detailed settings to the 9i.

Konica Minolta's AF/AE technology, developed through its expertise in camera manufacturing, relieves users from the need to determine the exact measuring distance. Moreover, the system automatically determines the optimum laser power for the surface conditions of the target. (Scan Range : standard mode 0.6 to 1.0 m, Extended mode 0.5 to 2.5 m)



#### Scanning the target with a laser beam

Take a measurement with the , Polygon Editing Tool (ver. 2.0 bundled) software.

#### High speed and high accuracy

Start the measurement by framing the scan area on the LCD Viewfinder of the VIVID 9i unit or on the host computer's display . Each scan requires only 2.5 seconds to aquire accurate 3D data.

#### Standards-Traceable performance

Konica Minolta supports compliance with ISO 9000. Manufacturers using VIVID 9i for QC applications can receive test report of the accuracy of each 9i, traceable to national standard. Thereby ensuring that our measuring instruments and your process conform to ISO 9000 requirements.

\*On request, Konica Minolta can provide a test report for each 9i unit. This test report is created by evaluating the measurement accuracy for all 3 lenses of each 9i using our Reference 3D Chart, an artifact traceable to national standards, and thus can be used as documentation for conformance with ISO requirements.



**Measurement with VIVID 9i** 

#### Merging and editing of 3D data

#### Quick, easy editing

Missed a spot? You'll see it immediately and be able to scan any voids. You can check the measured 3D data in real time on the preview screen. This allows for sequential framing, measurement, and alignment of the data. Thanks to the improved processing speed and the new graphical user interface specifically developed for the VIVID 9i, even large amounts of measurement data can be merged, edited and converted into general 3D data format with greater speed and ease.



What's more, our new field calibration system maintains the high reliability of the factory settings by canceling the degraded accuracy caused by lens exchange or a change in environment.





Merging of 3D data (polygons)

### Photogrammetry System PSC-1 optional

VIVID 9i captures large parts (> 1 meter) easily. When PSC-1 is used with the 9i, the combination enables the user to capture both high-detail and large parts. In the past, the alignment of multiple scans was error prone, making it hard to achieve high-detail and high accuracy on large parts. P-N automates the registration process, and removes the tolerance stack-up inherent in best-fit techniques.

When measuring a large part maximum detail is achieved by dividing the part into several scanned regions. With PSC-1 the individual scans are aligned (registered) automatically, with higher alignment accuracy than has been possible before. The procedure is described below:

#### Capture the image with a digital camera

Door

The user will place scale bars around the object to be scanned (the "subject") and attach reference markers to the subject. With the dedicated digital SLR, the operator takes pictures of the subject, being sure to include both the coded markers and dimension-controlled scale bars. Based on these pictures, the coordinates of the reference markers are determined with high accuracy using photogrammetric technology, creating a sparse point cloud of the subject (i.e., a 3D "Constellation" in the shape of the subject).



**PSC-1** Photographing scenario



#### Automatic alignment and merging of 3D data

Now it's time to scan the surface detail using the 9i. As each VIVID 9i scan is captured, it is automatically aligned to the PSC-1 data cloud created in step 1. The VIVID 9i reads the target data and places the scans in their correct orientation. Even relatively smooth shapes such as fenders or door skins are accurately aligned because the alignment does not depend on complex surface geometry. Result: a more accurate model.

In addition to being more accurate, PSC-1 saves time. Firstly, any voids are apparent immediately; aligned data enables the user to scan any missing surface data. Secondly, since the scans are aligned to the photogrammetric point cloud (rather than to each other), there is no need to overlap scans. Furthermore, if two areas of interest are separated by an unimportant area, the operator no longer needs to scan the intervening area, saving more time.



2

Example of procedure for CAD data creation — Creation of a CAD Model of an automotive alun



Example of CAT work procedure -

#### – Comparison inspection between measured data and CAI

#### Scanning the sample



#### Measured data (polygon)



Importing CAD data



Measurement, alignment, merging, and cleaning

-Comparison between reference CAD (NURBS) data and measured



#### Early detection of shape problems

#### Cross section/Grid display/Diagram dimensions/Errors at specifi



Inspection

**Evaluation at cross section** 

**Example of inspection evaluation report** 

#### tive aluminum casting

#### BS



atch matching the curve boundaries

#### **Trimmed NURBS surfaces**



Create geometrically shaped surfaces such as cones and planes. Trim the data with these surfaces.

#### **High-continuity surface data**



Example of continuous surface evaluation using environment mapping



#### Major applications

- $\bigcirc$  Automotive/motorcycle manufacturers and parts maker
- Dimensional inspection of cast/forged parts. Checking of the margin remaining for secondary processing
- Accuracy inspection, parts inspection, interference check with mechanical parts, die verification of press- or plastic-molded products
- Inspection/analysis of car seats, tires, and cushioning materials
  Reverse engineering using actual objects, mock-ups, and scale models of car seats, headrests or wheels
- Companies in heavy industry, iron/steel or heavy equipment manufacturers
   Inspection of turbine blades, steel pipes and steel plates. Design of heavy
- Inspection of turbine blades, steel pipes and steel plates. Design of ne equipment

 $\bigcirc$  Other manufacturers

- Inspection or reverse engineering of interior/exterior wall materials and modular bath units
- Inspection of train rail wear, tanks at hydroelectric power plants, and turbine blades
- For other applications, visit our website below

#### http://www.minolta3d.com

#### and CAD data —



#### l measured data—

#### s at specific points



### Alignment with CAD data



#### Color map calculation



## The non-contact 3D digitizer VIVID 9i offers improved accuracy and ease of use.

### High speed, high precision, and Measurement accuracy of $\pm \text{50}\mu\text{m}$

The VIVID 9i requires only 2.5 seconds per scan to acquire accurate 3D data.

Consequently, the VIVID 9i is ideal for accuracy verification and shape inspection of cast, forged, and pressed automotive parts and plastic-molded automotive parts. Give us your part, and we'll prove it to you.

The new Field Calibration system, negates inaccuracies caused by lens exchange or environmental changes. A simple calibration procedure before use assures the optimal performance from the 9i.

### High-accuracy measurement of even large parts

The VIVID 9i can be combined with PSC-1, Konica Minolta's optional photogrammetry system. The combination of the VIVID 9i and PSC-1provides for fast and accurate measurement and data assembly even for relatively large targets - such as car body portions, doors, bumpers, and instrument panels. It is also effective to correctly align surfaces having no characteristic shape, such as projections and depressions. (Typical subject size ranges from 0.5 to 2.0 m and larger)



#### <Measurement principle>

The VIVID 9i is based on the principal of laser triangulation. A target is scanned with laser stripes . The CCD camera receives the light reflected from the surface of the subject. Surface shape measurements of the subject are obtained through triangulation, and converted into a 3D polygon mesh. The VIVID 9i measures 640 x 480 points with one scan, simultaneously acquiring surface shape data and color image data.

### VIVID 9i system



#### < VIVID 9i Main standard accessories>

- 1 Interchangeable Lenses (TELE, MIDDLE, WIDE)
- 2 Field Calibration System
- Polygon editing software "Polygon Editing Tool ver.2.0"
- SCSI Cable

#### <Optional accessories>

- ③ Tripod Set
- Rotating Stage Set



#### **Specifications of VIVID 9i**

Туре	Non-contact 3D digitizer
Measuring Method	Triangulation light block method
Light-Receiving Lenses (Interchangeable)	TELE Focal distance f=25 mm
	MIDDLE Focal distance f=14 mm
	WIDE Focal distance f=8 mm
Scan Range	0.6 to 1.0 m (In Standard mode)
	0.5 to 2.5 m (In Extended mode)
Laser Scan Method	Galvanometer-driven rotating mirror
Laser Class	Class 2 (IEC60825-1), Class 1 (FDA)
X Direction Input Range(In Extended mode)	<b>TELE</b> 93 to 463 mm
	MIDDLE 165 to 823 mm
	<b>WIDE</b> 299 to 1495 mm
Y Direction Input Range(In Extended mode)	<b>TELE</b> 69 to 347 mm
	MIDDLE 124 to 618 mm
	<b>WIDE</b> 224 to 1121 mm
Z Direction Input Range(In Extended mode)	<b>TELE</b> 26 to 680 mm
	MIDDLE 42 to 1100 mm
	WIDE 66 to 1750 mm
Accuracy (X, Y, Z)	$\pm$ 0.05 mm (Using TELE lens at distance of 0.6 m, with Field Calibration System, Konica Minolta's standard, at 20°C)
Precision (Z, $\sigma$ )	0.008 mm (Using TELE lens at distance of 0.6 m, Konica Minolta's standard, at 20°C)
Input Time (per scan)	2.5 sec
Transfer Time to Host Computer	Approx. 1.5 sec
Ambient Lighting Condition	Office environment, 500 lx or less
Imaging Element	3D data: 1/3-inch frame transfer CCD (340,000 pixels)
	Color data: Common with 3D data (color separation by rotary filter)
Number of Output Pixels	3D data/Color data: 640 x 480
Output Format	3D data: Konica Minolta format, & (STL, DXF, OBJ, ASCII points, VRML)
	(Converted to 3D data by the Polygon Editing Software/ standard accessory)
	Color data: RGB 24-bit raster scan data
Data File Size	Total 3D and color data capacity: 3.6MB per data
Viewfinder	5.7-inch LCD (320 x 240 pixels)
Output Interface	SCSI II (DMA synchronous transfer)
Power	Commercial AC power, 100 to 240 V (50/60Hz), rated current 0.6 A (at 100 VAC)
Dimensions	221 (W) x 412 (H) x 282 (D) mm
Weight	Approx.15 kg (with lens attached)
Operating temperature/humidity range	10°C to 40°C, relative humidity 65% or less with no condensation
Storage temperature/humidity range	0°C to 40°C, relative humidity 85% or less (at 35°C) with no condensation
Regulatory approvals	UL 61010A-1, CSA-C22.2 No.1010-1, etc.

#### **Specifications of Polygon Editing Tool ver. 2.0**

<main features=""></main>		<
<b>Readable Formats</b>	Konica Minolta proprietary formats: CAM, VVD, SCN, CDM, CDK	Ρ
	General format: STL	C
Data Conversion	Conversion from Konica Minolta proprietary formats into general format	
	Polygonal data: DXF, Wavefront, Softimage, VRML 2.0, STL, MGF	C
	Point group data: ASCII	R
Functions	Data alignment, data merging, smoothing, uniform data reduction,	D
	adaptive data reduction, polygon check, texture blending	G
Point Group Editing	Rotation, movement, deletion, hole filling with data interpolation	
Camera Remote Operation	Measurement, measurement reference distance setting, number of scans setting, laser power setting, high-guality setting, filter setting,	s
	etc.	C

**Display Modes** Wireframe, shading, texture mapping

0.5 to 2.0 m

<operating environ<="" th=""><th>ment&gt;</th></operating>	ment>
PC-AT compatible	Computer running Windows <sup>®</sup> 2000/Windows <sup>®</sup> XP
OS	Windows*2000 Professional (Service Pack 2 or higher) Windows*XP Professional (Service Pack 1 or higher)
CPU	Pentium III or better
RAM	512 MB (1024 MB recommended)
Display	Graphic display ability at 1024 x 768 or more
Graphics Board	OpenGL-ready board (verified-compatible board recommended.)
SCSI Interface	Adaptec SCSI card
	(Please use a verified compatible board.)
Others	CD-ROM drive, USB port

For further information regarding graphics board and SCSI interface, please contact the Vivid Salesperson in your area.

#### **Specifications of Photogrammetry System PSC-1**

**Typical Subject Size** Accuracy

±0.1 mm for volume <2 m<sup>3</sup> and below (Measurement subject size : 1 m, Photogrammetry alone, Konica Minolta's standard, at 20°C)



Konica Minolta Photo Imaging U.S.A., Inc.

EMail: VIVID3d@minolta.com Web: www.minolta3d.com

Room 1818, Sun Hung Kai Centre, 30 Harbour Road, Wanchai, Hong Kong Phone: 852-34137508 FAX: 852-34137509 Konica Minolta Photo Imaging Asia HQ Pte Ltd. 10, Teban Gardens Crescent, Singapore 608923 Phone: +65 6563-5533 FAX: +65 6560-9721

Konica Minolta Photo Imaging (HK)Ltd. ©2004 KONICA MINOLTA SENSING, INC.